



B


A



Notes:


- 1) Current Rating: 1A
- 2) Voltage Rating: 60V
- 3) Contact Resistance: 5mΩ MAX
- 4) Insulation Resistance: 100MΩ MIN
- 5) Withstanding Voltage: 500V AC/Min
- 6) Waterproof rate: IP67
- 7) Operating Temperature Range: -20°C ~ 80°C
- 3) Material and finish:
 - Nylon Insulator, UL94V-0 Black
 - Copper Alloy Terminal, Gold Plated (4)
 - Silicone Seal Ring, Green
 - Copper Alloy Nut, Nickel Plated
- 4) RoHS Compliant

PIN Assignment Front View



SS-12600-003


PART NUMBER



DO NOT SCALE DRAWING
DRAWING IS SUBJECT TO
CHANGE WITHOUT NOTICE

DIMENSIONS: METRIC

SHEET NO.
1 OF 1



stewart
CONNECTOR
a bel group

11118 Susquehanna Trail South
Glen Rock, PA 17327-9199
(717) 235-7512
<http://www.stewartconnector.com>

TITLE
M5 PLUG, FEMALE, SOLDER TYPE FOR OVERMOLDING

THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON
ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF
STEWART CONNECTOR AND SHALL NOT BE REPRODUCED,
COPIED, OR USED IN ANY MANNER WITHOUT PRIOR WRITTEN
CONSENT OF STEWART CONNECTOR. ONE OR MORE U.S. PATENTS
MAY APPLY TO THIS PRODUCT. FOR DETAILS, PLEASE
VISIT: [HTTP://BELFUSE.COM/STEWART/STEWART_PATENTS/](http://BELFUSE.COM/STEWART/STEWART_PATENTS/)

DRN BY:	ARC	DATE	11/24/23
APPD BY:	GWL	DATE	11/24/23
DWG NO.	CT120035	REV.	A0

B

A