



NOTES: UNLESS OTHERWISE SPECIFIED.

1. MATERIALS & FINISH:

- 1.1 HOUSINGS & NUT: PASSIVATED STAINLESS STEEL.
- 1.2 CENTER CONTACT: GOLD PLATED BERYLLIUM COPPER.
- 1.3 DIELECTRIC: PTFE (TEFLON).
- 1.4 SUPPORT BEAD: NORYL
- 1.5 GASKET: SILICONE RUBBER
- 1.6 RETAINING RINGS: UNPLATED BERYLLIUM COPPER

2. ELECTRICAL SPECIFICATION:

- 2.1 FREQUENCY RANGE: DC TO 18.0 GHz
- 2.2 VSWR (MAX)
 - DC TO 4.0 GHz: 1.04:1
 - 4.0 TO 8.0 GHz: 1.07:1
 - 8.0 TO 18.0 GHz: 1.12:1
- 2.3 IMPEDANCE: 50 OHMS

<p>This PROPRIETARY Document is property of Cinch Connectivity Solutions. It is confidential in nature, non-transferable, and issued with the clear understanding that it is not to be traded or copied without permission and is returnable upon demand.</p> <p>INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2009.</p>	<p>3RD ANGLE PROJECTION</p>	MIDWEST MICROWAVE	
	<p>RoHS2 <input checked="" type="checkbox"/></p> <p>2011/65/EU</p>	<p>Title: ADAPTER N JACK/3.5MM PLUG</p>	
<p>UNLESS OTHERWISE SPECIFIED</p> <p>.XX ±.02</p> <p>.XXX ±.005</p> <p>ANGLES ±2°</p>	<p>Model No.</p> <p style="text-align: center;">ADT-2714-NF-3MM-02-01</p>		
<p>Size A</p>	<p>DO NOT SCALE DRAWING</p>	<p>Date: 11/5/2014</p>	<p>Sheet 1 of 1</p>