


2X SMA MALE
PER MIL-STD- 348
FIGURE 310-1

5/16 HEX




NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIALS AND FINISH

- 1.1 BODY AND CENTER CONTACT: GOLD PLATED BRASS
- 1.2 INSULATOR: PTFE

2. ELECTRICAL SPECIFICATIONS

- 2.1 FREQUENCY RANGE: DC TO 18 GHz
- 2.2 IMPEDANCE: 50 OHMS NOMINAL
- 2.3 VSWR (MAXIMUM): 1.25 : 1

	3RD ANGLE PROJECTION 	MIDWEST MICROWAVE	
NOTICE: The information in this drawing is PROPRIETARY and must not be used without the permission of Cinch Connectivity Solutions. It may contain data whose export is restricted. Verify status prior to exporting. INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2018		RoHS2 ☒ 2015/863/EU UNLESS OTHERWISE SPECIFIED UNITS: INCH .FXX ±.02 FRACTIONS ±1/64 ANGLES ±2°	Title: SMA MALE TO MALE ADAPTOR Model No. CGM-1180-MM-SMA-09 Size A DO NOT SCALE DRAWING Date: 05/20/2021 Sheet 1 OF 1