


TABLE 1	
MODEL NUMBER	LENGTH
415-0573-006	6.00±.15
415-0573-012	12.00±.25

REV	ECO	DATE
1	INITIAL RELEASE	03/18/2025



PART LIST		
ITEM	QTY	DESCRIPTION
1	1	SMPM FEMALE
2	2 X1.00±.10	HEAT SHRINK TUBING
3	AR	CABLE
4	1	SMA MALE

NOTES: UNLESS OTHERWISE SPECIFIED.

1. CABLE ASSEMBLY DIELECTRIC WITHSTANDING VOLTAGE:
500 VRMS FOR A PERIOD OF ONE MINUTE.
2. CABLE ASSEMBLIES TO BE 100% TESTED FOR VOLTAGE AND CONTINUITY.
3. ASSEMBLIES TO BE PACKAGED 1 PER BAG.
4. VSWR: 1.35 MAX DC-26.5GHZ

This PROPRIETARY Document is property of Cinch Connectivity Solutions. It is confidential in nature, non-transferable, and issued with the clear understanding that it is not traced or copied without permission and is returnable upon demand. INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2018.	Model No:	415-0573-001/999		JOHNSON	
	RoHS ☒ (EU)/2015/863 COMPLIANT	Cage Code	34078	Title: CABLE ASSY. STR SMPM FEMALE TO STR SMA MALE, .086" FLEXIBLE	
	UNLESS OTHERWISE SPECIFIED UNITS: INCH	3RD ANGLE PROJECTION		Drawing No.	REV.
	.XX ± .01 .XXX ± .003 .XXXX ± .0010 ANGLE ± 2°	Drawn by: JIMMY CHEN	Date: 03/18/2025	415-0573-001/999	1
		Size A	DO NOT SCALE DRAWING	Workmanship Std: NONE	1 OF 1