RED INDICATES ORIGINAL

DATA CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO TROMPETER ELECTRONICS INC. AND SHALL NOT BE DISCLOSED, COPIED OR USED FOR PROCUREMENT OR MANUFACTURE WITHOUT EXPRESS WRITTEN PERMISSION.

REVISIONS			3-0018	SH 1
REV	ECO	DESCRIPTION	DWN / APPROVED	DATE
AJ	11485	FOR CHANGES SEE ECO	AAH / Bm / FR	1/19/96

TABLE 1		
DASH NO	CABLES ACCOMMODATED	ASSEMBLE PER
-7	TRC-50-2/TRC-75-2	TAI-189
-9	TWC-78-2/TWC-124-2	TAI-102
-23	250-3884, MICRODOT	TAI-189
-24	202-3934, MICRODOT	TAI-102
-24A	9530A5117, RAYCHEM	TAI-189
-25	T-434, GENERAL	TAI-102
-25A	5021H5331, RAYCHEM	TAI-188
-26	7028A5518, RAYCHEM	
-27	202-3927, MICRODOT	TAI-102
-29	TWC-78-1/TWC-124-1A	
-30	751A, W.E.CO./8441, BELDEN	
-32	TRC-50-1	TAI-189
-33	TRC-75-1	
-42	21-204, ESSEX 4463, CONSOLIDATED	
-43	250-4044/250-4045 283-3930, MICRODOT	
-45	M27500-22TE2T14 1100-66F, STANDARD	TAI-102
-47	M17/176-00002	
-49	TWAC-78-1F2	
-55	89272, BELDEN	
-58	GC875GC1, GRUMMAN	TAI-189
-57	GC875G81, GRUMMAN	
-58	GC875TM24H, GRUMMAN	TAI-102
-59	GC875LN1, GRUMMAN	
-60	M17/177, THERMATICS 380-10045, BOEING	TAI-189
-64	7528A5314, RAYCHEM	

TABLE 3 POLARIZATION CHART				
KEYING LETTER	A DEGREES	B DEGREES	C DEGREES	COLOR BAND
NONE	120°	120°	120°	NONE
T	100°	150°	110°	RED
U	120°	130°	110°	ORANGE
V	115°	130°	115°	YELLOW
W	125°	110°	125°	GREEN
X	130°	100°	130°	BLUE
Y	110°	140°	110°	VIOLET
Z	100°	160°	100°	GRAY
S	135°	135°	90°	WHITE



-7 SHOWN

FIG 1



INCH	MM
.005	0.13
.096	2.44
.125	3.18
.132	3.35
.145	3.68
.160	4.06
.164	4.17
.189	4.85
.191	4.85
.198	5.03
.200	5.08
.217	5.51
.218	5.54
.221	5.61
.235	5.97
.250	6.35
.274	6.96
.285	7.24
.300	7.62
.437	11.10
.500	12.70
.505	12.83
.510	12.95
.625	15.88
.687	17.45
.722	18.34
.800	20.32
1.314	33.38
1.845	46.88

TABLE 2 ⚠6		
MILITARY PART NO (PIN)	MILITARY CABLE PART NO	TROMPETER PART NO (REF ONLY) ⚠6
M49142/05-0001	M17/134-00001	M3-0018-7
M49142/05-0101	M17/134-00001	M3-0018Y-7
M49142/05-0201	M17/134-00001	M3-0018S-7
M49142/05-0002	M17/134-00002	M3-0018-7
M49142/05-0102	M17/134-00002	M3-0018Y-7
M49142/05-0202	M17/134-00002	M3-0018S-7
M49142/05-0007	M17/45-RG108	M3-0018-9
M49142/05-0107	M17/45-RG108	M3-0018Y-9
M49142/05-0207	M17/45-RG108	M3-0018S-9
M49142/05-0008	M17/176-00002	M3-0018-47
M49142/05-0108	M17/176-00002	M3-0018Y-47
M49142/05-0208	M17/176-00002	M3-0018S-47
M49142/05-0009	M17/177-00001	M3-0018-60
M49142/05-0109	M17/177-00001	M3-0018Y-60
M49142/05-0209	M17/177-00001	M3-0018S-60



-7 SHOWN

FIG 2 ⚠5





CABLE ENTRY			
DASH NO	DIA	DASH NO	DIA
-7	.274	-33	.217
-9	.285	-42	.300
-23	.183	-43	.200
-24	.191	-45	.183
-24A	.200	-47	.164
-25	.285	-49	.132
-25A	.285	-55	.250
-26	.189	-56	.191
-27	.145	-57	
-28	.191	-58	.198
-30	.235	-59	
-32	.191	-60	.217

⚠6 WHEN CONNECTOR IS SUPPLIED TO MILITARY PART NO (SEE TABLE 2):

a) ALL PARTS NORMALLY PLATED TFS-1A OR TFS-1U (NICKEL) ARE TO BE PLATED TFS-1M (SILVER)

b) MARK PART WITH MILITARY PIN (SEE TABLE 2) AND "14949"

c) QUALITY CONFORMANCE INSPECTION SHALL BE PER MIL-C-49142 SECTION 4.5

⚠5 IF BEND RELIEF SPRING REQD ADD SUFFIX "BR" TO MODEL NO (SEE FIG 2)

4. CONCENTRIC TWINAX/TRIAX TR8 BULKHEAD MOUNT CABLE RECEPTACLE
3. MAX PANEL THK .160
2. FINISH: TFS-1A (NICKEL) ⚠6
1. ALL DIM ARE IN INCHES

7. EXAMPLE OF COMPLETE MODEL NO:

8J79 T-7

8J79 — BASIC MODEL NO
T — POLARIZATION LETTER (SEE TABLE 3)
-7 — DASH NO

305-0522	QTY	DESCRIPTION		PART NUMBER	ITEM
305-0521		TOL UNLESS SPECIFIED .XX ± .005, .XXX ± .010, ANGLES ±	TROMPETER RF connectivity	8J79/T/V/W/X/Y/Z/S/BR	
305-0458					
305-0404	DWN	AAH	1-13-86	MATERIAL	CODE IDENT 14949
305-0382	CHK	Bm	1-18-96		DRAWING NO. 3-0018
205-0030	ENGR				REV AJ
NEXT ASSY	APPR	FR	1/19/96	SCALE 2/1	DATE 4/13/87 SHEET 1 OF 2
305-0575					
305-0534					
210-0003					

Please read our datasheet & drawing disclaimer here.