

RED INDICATES ORIGINAL


DATA CONTAINED IN THIS DOCUMENT IS
PROPRIETARY TO TROMPETER ELECTRONICS INC.
AND SHALL NOT BE DISCLOSED, COPIED OR USED
FOR REPRODUCTION OR MANUFACTURE WITHOUT
EXPRESS WRITTEN PERMISSION.

REVISIONS			3-0228	SH 1
REV	ED	DESCRIPTION	OWN	APPROVED
L	12382	ADDED -224 & -225; SEE ECD	DEN	MM MM 5/18/98

DASH NO	CABLES ACCOMMODATED	A DIM	B DIA	C HEX	ASSEMBLE PER
-201	M17-176-00002				
-202	TWC-78-1				
-203	TWC-124-1A				
-204	10802, RAYCHEM	1.184	.349	.255	TAI-143
-205	TWC-78-1F2				
-206	782800130, RAYCHEM				
-207	89310 BELDEN	1.288	.452	.344	TAI-167
-208	202-3927 MICRODOT				
-209	202-3942 MICRODOT	1.164	.349	.255	TAI-143
-210	8451 BELDEN				TAI-167
-211	202-3934 MICRODOT				
-212	2524E0114, RAYCHEM				
-213	TWC-78-2	1.289	.452	.344	TAI-144
-214	TWC-124-2				
-215	BL-982 TIMES				
-216	BL-1242 TIMES				
-217	6C875TM24H, GRUMMAN				
-218	EPD 2218B8, RAYCHEM				
-219	252801114, RAYCHEM				
-220	6C875RR1, GRUMMAN	1.164	.349	.255	TAI-143
-221	10514, RAYCHEM				
-222	10813, RAYCHEM				
-223	HMS2-114B, HUGHES				
-224	TWCP-124-3	1.289	.452	.344	TAI-144
-225	P5685PL, PRIME STOCK				

DASH NO	CABLES ACCOMMODATED	A DIM	B DIA	C HEX	ASSEMBLE PER
-301	6C875GC1, GRUMMAN				
-302	6C875GB1, GRUMMAN 5022E5111, RAYCHEM	1.164	.349	.255	TAI-157
-303	7528A5314, RAYCHEM				
-304					
-305	M17-177-00001 285-3804 MICRODOT	1.289	.452	.344	TAI-173
-306	TRC-50-2 M17-134-00002				
-307	TRC-75-1	1.288	.452	.344	TAI-198
-308	TRC-75-2				TAI-173
-309	TRC-50-1	1.164	.349	.255	TAI-157


INCH	MM
.005	0.13
.030	0.76
.255	6.48
.344	8.74
.349	8.87
.452	11.48
1.00	25.40
1.25	31.75
1.164	29.57
1.289	32.74
1.75	44.45



-207 SHOWN

1. SHRINKABLE STRAIN RELIEF AND/OR SHRINKABLE SEALING SLEEVE SUPPLIED LOOSE AS FOLLOWS:
- CABLE GROUPS -207, -210 & -307:
1 SHRINKABLE STRAIN RELIEF (1.00 LONG)
1 SHRINKABLE SEALING SLEEVE (1.25 LONG)
 - CABLE GROUPS -201 THROUGH -206, -208, -209, -217 THROUGH -223, -301, -302, -303 & -309:
1 SHRINKABLE SEALING SLEEVE (1.25 LONG)
 - CABLE GROUPS -211 THROUGH -216, -305, -306 & -308:
1 SHRINKABLE STRAIN RELIEF (1.75 LONG)
2. FINISH: TFS-1A (NICKEL)
3. 3-LUG SUBMINIATURE CONCENTRIC TWINAX (4 PIECE ASSY) AND TRIAX (6 PIECE ASSY), FULL CRIMP CABLE PLUG
4. ALL DIM ARE IN INCHES

6. EXAMPLE OF COMPLETE MODEL NO:
CJ3150AC-201
- BASIC MODEL NO. CABLE GROUP DASH NO
5. EXAMPLE OF COMPLETE PART NO:
3-0228-201
- BASIC PART NO. CABLE GROUP DASH NO



RECOMMENDED
HEX CRIMP
SCALE: NONE

QTY	DESCRIPTION	PART NUMBER	ITEM
TOL UNLESS SPECIFIED REF 2-03 .004 2-005 .00002 UNLESS	TROMPETER RF connectivity	CJ3150AC	
DWN DBN 4/23/98 CHK IN-1 4-24-98 ENGR	MATERIAL CODE IDENT 14949	DRAWING NO. 3-0228	REV L
NEXT ASSY	APPROVAL	SCALE 4/1	DATE 5-31-85 SHEET 1 OF 2