DATA CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO EMERSON CONNECTIVITY SOLUTIONS AND SHALL NOT BE DISCLOSED, COPIED OR USED FOR PROCUMENT OR MANUFACTURE WITHOUT EXPRESS WRITTEN PERMISSION

REVISIONS

REV	DESCRIPTIONS	DATE	APPROVED
BS	ECO 52461	6/18/10	C.MONAHAN

TABLE 1

DASH NO	CABLES ACCOMMODATED	A DIM	B DIM	C FLATS	D FLATS	E DIA	CABLE ENTRY DIA	ASSEMBLE PER	CABLE TYPE
-7	TRC-50-2, MI7/134-00001 TRC-75-2	1.135	.096	.438	.438	.500	.274	TAI-189	TRIAX
-8	8227, BELDEN	1.716	.130	.625	.688	.750	.345	TAI-103	TWINAX
-9	TWC-78-2 TWC-124-2, MI7/45-RG 308	1.135	.096	.438	.438	.500	.285	TAI-102	TWINAX
-A9	BL782, TIMES BL982, TIMES BL1242, TIMES		△3	△3					
-10	RG-22 754E, AT&T	1.716	.130	.625	.688	.750	.455	TAI-103	TWINAX
-11	760A, AT&T						.345		
-12	16PEVL, AT&T VI-AL, GENERAL						.485	TAI-128	
-13	TRF-59, TIMES						.362	TAI-129	TRIAX
-13A	8232, BELDEN						.352	TAI-165	
-14	8233, BELDEN						.510	TAI-129	
-23	250-3884, MICRODOT	1.135	.096	.438	.438	.500	.183	TAI-189	TRIAX
-24	202-3934, MICRODOT						.191	TAI-102	TWINAX
-24A	9530A5117, RAYCHEM						.200	TAI-189	TRIAX
-25	T-43M, GENERAL						.285	TAI-102	TWINAX
-25A	5021H5331, RAYCHEM							TAI-189	TRIAX
-26	7028A5518, RAYCHEM						.183		
-27	T19TPSJ2619EN, WOVEN 202-3927, MICRODOT 202-3942, MICRODOT						.145	TAI-102	TWINAX
-29	TWC-78-1/TWC-124-1A						.191		
-30	761A, AT&T 8441, BELDEN						.235		
-32	TRC-50-1						.191	TAI-189	TRIAX
-33	TRC-75-1						.217		
-42	21-204, ESSEX 4463, CONSOLIDATED						.300		
-43	250-4044/250-4045 293-3930, MICRODOT						.200		
-45	M27500-22TE2T14 1100-66F, STANDARD						.183	TAI-102	TWINAX
-46	9860, BELDEN	1.716	.130	.625	.688	.750	.475	TAI-103	
-47	MI7/176-00002	1.135	.096	.438	.438	.500	.164	TAI-102	
-49	TWAC-78-1F2						.132		
-54	89207, BELDEN	1.716	.130	.625	.688	.750	.323	TAI-103	
-55	89272, BELDEN	1.135	.096	.438	.438	.500	.250	TAI-102	
-56	GC875GC1, GRUMMAN						.191	TAI-189	TRIAX
-57	GC875GB1, GRUMMAN								
-58	GC875TM24H, GRUMMAN						.198	TAI-102	QUADRAX
-59	GC875LN1, GRUMMAN								
-60	MI7/177-00002, THERMATICS 380-10045, BOEING						.217	TAI-189	TRIAX
-64	7528A5314, RAYCHEM						.183		

TABLE 3

KEYING LETTER	F DEGREES	G DEGREES	H DEGREES	COLOR BAND
NONE	120°	120°	120°	NONE
T	100°	150°	110°	RED
U	120°	130°	110°	ORANGE
V	115°	130°	115°	YELLOW
W	125°	110°	125°	GREEN
X	130°	100°	130°	BLUE
Y	110°	140°	110°	VIOLET
Z	100°	160°	100°	GRAY
S	135°	135°	90°	WHITE



FIG 2
PL75-9 SHOWN





SCALE 1/2

FIG 1
PL75-9BR SHOWN △4



5. EXAMPLE OF COMPLETE MODEL NO:

PL75 T -9 BR △4

- PL75 — BASIC MODEL NO
- T — POLARIZATION LETTER NONE REQD FOR STD POLARIZATION (SEE TABLE 3)
- -9 — DASH NO (CABLE GROUP, SEE TABLE 1)
- BR — BEND RELIEF (OMIT IF NOT REQD)

△4 IF BEND RELIEF SPRING REQUIRED (SEE FIG 1) ADD SUFFIX "BR" TO MODEL NUMBER (NOT AVAILABLE WITH CABLE GROUPS -8, -10, -11, -12, -13, -13A, -14, -46, & -54)

△3 CLAMP NUT OMITTED

2. CONCENTRIC TWINAX/TRIAX 3-LUG TRB CABLE PLUG

1. PLATING: 310-0002-XX — PER TFS-1 OR -U FOR UNPLATED

NOTES: UNLESS OTHERWISE SPECIFIED.

INTERPRET DRAWING PER MIL-STD-100. DIMENSIONS ARE IN INCHES AND INCLUDE FINISH THICKNESS UNLESS OTHERWISE SPECIFIED.

TOL: UNLESS SPECIFIED. .XX ± .02 .XXX ± .010 ANGLE ± 1°

DRN	M. JOHNSON	3-18-09
CHK	LM	4/1/09
QUALITY		
MANUF		
APPROVED		
PRO/E FILE NO.	310-0002	

MATERIAL:

FINISH:

DO NOT SCALE DWG

N/A	
BLANK LENGTH (REF. ONLY)	
N/A	
SURFACE AREA	

cinch CONNECTIVITY SOLUTIONS a bel group
Cinch Connectivity Solutions
299 Johnson Ave. Ste. 100
Waseca, MN 56093
1-800-247-8256

TITLE: PL75/T/U/V/W/ X/Y/Z/S/BR

SIZE	CAGE CODE	DRAWING NO.	REV.
A	14949	310-0002	BS

SCALE	DATE	SHEET
1/1	1-12-66	1 OF 2

Please read our datasheet & drawing disclaimer here.