




REV	ECO	DATE
001	58545	03/08/2023



NOTES: UNLESS OTHERWISE SPECIFIED.

1. MATERIALS & FINISH: SEE SHEET 2

2. ELECTRICAL SPECIFICATIONS:

2.1 FREQUENCY RANGE: DC-18 GHz

2.2 IMPEDANCE: 50 OHMS NOMINAL

2.3 VSWR (MAX): 1.05±0.01F (GHz)

2.4 POWER HANDLING CAPABILITY:

2.4.1 AVERAGE: 0.5 WATTS MAX AT 25°C
DERATED LINEARLY TO 0.125 WATTS
AT 125°C

2.4.2 PEAK: 50 WATTS

2.5 OPERATING TEMPERATURE RANGE: -55°C TO 125°C

2.6 WEIGHT (MAX): .25 oz

3. SCREENING PARAMETERS PER ATP-09418-60-02, LEVEL C.

 NOTICE: The information in this drawing is PROPRIETARY and must not be used without the permission of Cinch Connectivity Solutions. It may contain data whose export is restricted. Verify status prior to exporting. INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2018	Model No:	SQT-0180-M0-SMA-02		MIDWEST MICROWAVE	
	RoHS2	☒	Cage Code	34078	Title
	2015/863/EU		3RD ANGLE PROJECTION		SPACE TERMINATION
	UNLESS OTHERWISE SPECIFIED UNITS: INCH		ENGINEER:	J. KEREKES	Drawing No.
	.XX ±.02		Date:	02/09/2023	SQT-0180-M0-SMA-02-01
	.XXX ±.010		Size	A	DO NOT SCALE DRAWING
	ANGLES ±2°		Workmanship Std:		Sheet 1 OF 2
			Rev.		001

REV	ECO	DATE
001	58545	03/08/2023

ITEM	QTY	DESCRIPTION	MATERIAL	FINISH/OUTGASSING
1	1	COUPLING NUT	STAINLESS STEEL PER ASTM-A582, TYPE 303	PASSIVATED PER SAE AMS2700, METHOD 2
2	1	GASKET	VITON A FLUOROELASTOMER PER SAE AMS7276	N/A
3	1	RETAINING RING	BERYLLIUM COPPER PER ASTM-B197, ALLOY C172	N/A
4	1	SMA MALE CONTACT	BERYLLIUM COPPER PER ASTM-B196, ALLOY C173	50 MICROINCHES MIN GOLD PLATE PER ASTM-B488, TYPE II, GRADE C, CLASS 1.27
5	1	DIELECTRIC	PTFE TYPE 1, GRADE 1, CLASS B, PER ASTM D 1710	N/A
6	1	SMA MALE HOUSING	STAINLESS STEEL PER ASTM-A582, TYPE 303	PASSIVATED PER SAE AMS2700, METHOD 2
7	1	SHIM	STAINLESS STEEL PER ASTM-A582, TYPE 303	PASSIVATED PER SAE AMS2700, METHOD 2
8	1	BUSHING	STAINLESS STEEL PER ASTM-A582, TYPE 303	PASSIVATED PER SAE AMS2700, METHOD 2
9	2	EDGE SPRING	BERYLLIUM COPPER PER ASTM-B194, ALLOY C172	20 MICROINCHES MIN GOLD PLATE PER ASTM-B488, TYPE II, CLASS 0.5, GRADE B OR C.
10	1	CARD SPACER	BERYLLIUM COPPER PER ASTM-B196, ALLOY C173	20 MICROINCHES MIN GOLD PLATE PER ASTM-B488, TYPE II, CLASS 0.5, GRADE B OR C.
11	1	RESISTOR CARD	TANTALUM NITRIDE THIN FILM OVER ALUMINUM NITRIDE CERAMIC	40 MICROINCHES MIN GOLD SPUTTERED TERMINALS PER MIL-G-45204, TYPE III, GRADE A
12	1	CENTER PLUNGER	BERYLLIUM COPPER PER ASTM-B194, ALLOY C172	20 MICROINCHES MIN GOLD PLATE PER ASTM-B488, TYPE II, CLASS 0.5, GRADE B OR C.
13	1	PLUNGER SPRING	BERYLLIUM COPPER PER ASTM-B194, ALLOY C172	50 MICROINCHES MIN GOLD PLATE PER ASTM-B488, TYPE II, GRADE C, CLASS 1.27
14	1	SUPPORT BEAD	ULTEM 1000 PER ASTM D7293 S-PEI0111	N/A
15	1	END PLUG	STAINLESS STEEL PER ASTM-A582, TYPE 303	PASSIVATED PER SAE AMS2700, METHOD 2
16	A/R	EPOXY SEAL	3M SCOTCH-WELD 2214 NMF (1-HOUR CURE @ 125°C)	TML%=0.77, CVCN%=0.02
17	A/R	BLACK MARKING INK	VIDEOJET 16-5900 (1-HOUR MIN CURE @ 175 °C)	TML%=0.74, CVCN%=0.04

 NOTICE: The information in this drawing is PROPRIETARY and must not be used without the permission of Cinch Connectivity Solutions. It may contain data whose export is restricted. Verify status prior to exporting. INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2018	Model No:	SQT-0180-M0-SMA-02		MIDWEST MICROWAVE		
	RoHS2	☒	2015/863/EU	Title: SPACE TERMINATION		
	UNLESS OTHERWISE SPECIFIED UNITS: INCH	3RD ANGLE PROJECTION	Cage Code	34078	Drawing No.	SQT-0180-M0-SMA-02-01
	ENGINEER:	J. KEREKES	Date:	02/09/2023	Size	A
DO NOT SCALE DRAWING		Workmanship Std:	Sheet: 2 OF 2			